

Safety Data Sheet

according to Regulation (EC) No 1907/2006

MET-L-CHEK Developer D70 Spray

Revision date: 05.06.2023

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

MET-L-CHEK Developer D70 Spray

Further trade names

Article no. (user):
121.100.501

UFI: CFK5-3XE2-9Q6R-V25U

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Inspection of metals

1.3. Details of the supplier of the safety data sheet

Company name:	Helling GmbH	
Street:	Spoekerdamm 2	
Place:	D-25436 Heidgraben	
Telephone:	+49-4122-922-0	Telefax: +49-4122-922-201
e-mail:	info@helling.de	
Internet:	www.helling.de	

1.4. Emergency telephone number: Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Hazard categories:
Aerosols: Aerosol 1
Serious eye damage/eye irritation: Eye Irrit. 2
Specific target organ toxicity - single exposure: STOT SE 3
Hazard Statements:
Extremely flammable aerosol.
Pressurised container: May burst if heated.
Causes serious eye irritation.
May cause drowsiness or dizziness.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

MET-L-CHEK Developer D70 Spray

Revision date: 05.06.2023

Page 2 of 11

Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to industrial incineration plant.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
106-97-8	butane			40 - 50 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1; H220			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			22 - 44 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
74-98-6	propane			6 - 10 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1; H220			
75-28-5	isobutane			2 - 4 %
	200-857-2	601-004-00-0		
	Flam. Gas 1; H220			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
106-97-8	203-448-7	butane	40 - 50 %
		inhalation: LC50 = 658 mg/l (dusts or mists)	
67-63-0	200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	22 - 44 %
		inhalation: LC50 = 30 mg/l (dusts or mists); dermal: LD50 = 13400 mg/kg; oral: LD50 = 4570 mg/kg	
74-98-6	200-827-9	propane	6 - 10 %
		inhalation: LC50 = > 20 mg/l (vapours)	

SECTION 4: First aid measures

4.1. Description of first aid measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

MET-L-CHEK Developer D70 Spray

Revision date: 05.06.2023

Page 3 of 11

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

Wash with plenty of water. Change contaminated clothing.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

Following inhalation: Headache. drowsiness. Dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

6.3. Methods and material for containment and cleaning up**Other information**

Ventilate affected area.

Flammable liquids: Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

MET-L-CHEK Developer D70 Spray

Revision date: 05.06.2023

Page 4 of 11

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. When using do not eat or drink. After work, wash hands and face.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition - No smoking.

Hints on joint storage

Do not store together with: Oxidising agent

7.3. Specific end use(s)

Inspection of metals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	89 mg/m³
Worker DNEL, long-term		inhalation	systemic	500 mg/m³

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Safety Data Sheet

according to Regulation (EC) No 1907/2006

MET-L-CHEK Developer D70 Spray

Revision date: 05.06.2023

Page 5 of 11

Eye/face protection

Wear eye/face protection.

Hand protection

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Recommended protective gloves brand: NR (Natural rubber (Caoutchouc), Natural latex).

Protect skin by using skin protective cream.

Skin protection

Body protection: not required.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Environmental exposure controls

No information available.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Aerosol
Colour:	white
Odour:	characteristic
Melting point/freezing point:	not applicable
Boiling point or initial boiling point and boiling range:	not applicable
Flammability	
Solid/liquid:	not applicable
Gas:	not applicable
Lower explosion limits:	1,4 vol. %
Upper explosion limits:	10,8 vol. %
Flash point:	not applicable
Decomposition temperature:	not determined
pH-Value:	not applicable
Water solubility:	slightly soluble
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	3100 hPa
(at 20 °C)	
Density (at 20 °C):	0,925 g/cm ³
Relative vapour density:	not determined

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

Heating causes rise in pressure with risk of bursting. Vapours may form explosive mixtures with air.

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

Not oxidising.

Other safety characteristics

Evaporation rate:

not determined

Safety Data Sheet

according to Regulation (EC) No 1907/2006

MET-L-CHEK Developer D70 Spray

Revision date: 05.06.2023

Page 6 of 11

Solid content:

0%

SECTION 10: Stability and reactivity

10.1. Reactivity

No risks worthy of mention.

10.2. Chemical stability

No risks worthy of mention.

10.3. Possibility of hazardous reactions

Vapours may form explosive mixtures with air.

10.4. Conditions to avoid

Remove all sources of ignition. Keep away from heat.

10.5. Incompatible materials

Oxidizing agents.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (inhalation gas) 1468,7 ppm

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
106-97-8	butane				
	inhalation (4 h) dust/mist	LC50 658 mg/l	Rat		
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 4570 mg/kg	Rat		
	dermal	LD50 13400 mg/kg	Rabbit		
	inhalation (4 h) dust/mist	LC50 30 mg/l	Rat		
74-98-6	propane				
	inhalation (4 h) vapour	LC50 > 20 mg/l	Rat		

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

MET-L-CHEK Developer D70 Spray

Revision date: 05.06.2023

Page 7 of 11

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

see section 12

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

Aquatic toxicity: No data available

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 8970 mg/l	96 h	Leuciscus idus (golden orfe)		
	Acute algae toxicity	ErC50 >1000 mg/l	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna		
	Acute bacteria toxicity	(EC50 >100 mg/l)				
74-98-6	propane					
	Acute fish toxicity	LC50 > 100 mg/l	96 h			
	Acute algae toxicity	ErC50 > 100 mg/l				
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h			

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
74-98-6	propane	2,36
75-28-5	isobutane	2,8

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The product has not been tested.

12.7. Other adverse effects

No information available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

MET-L-CHEK Developer D70 Spray

Revision date: 05.06.2023

Page 8 of 11

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number or ID number:**

UN 1950

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es):

2

Hazard label:

2.1



Classification code:

5F

Special Provisions:

190 327 344 625

Limited quantity:

1 L

Transport category:

2

Tunnel restriction code:

D

Other applicable information (land transport)**Inland waterways transport (ADN)****14.1. UN number or ID number:**

UN 1950

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es):

2

Hazard label:

2.1



Classification code:

5F

Special Provisions:

190 327 344 625

Limited quantity:

1 L

Other applicable information (inland waterways transport)**Marine transport (IMDG)****14.1. UN number or ID number:**

UN 1950

14.2. UN proper shipping name:

AEROSOLS

Safety Data Sheet

according to Regulation (EC) No 1907/2006

MET-L-CHEK Developer D70 Spray

Revision date: 05.06.2023

Page 9 of 11

14.3. Transport hazard class(es):

2.1

14.4. Packing group:

-

Hazard label:

2.1



Special Provisions:

63, 190, 277, 327, 344, 959

Limited quantity:

See SP277

EmS:

F-D, S-U

Other applicable information (marine transport)

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:

UN 1950

14.2. UN proper shipping name:

AEROSOLS, flammable

14.3. Transport hazard class(es):

2.1

Hazard label:

2.1



Special Provisions:

A145 A167 A802

Limited quantity Passenger:

30 kg G

IATA-packing instructions - Passenger:

203

IATA-max. quantity - Passenger:

75 kg

IATA-packing instructions - Cargo:

203

IATA-max. quantity - Cargo:

150 kg

Other applicable information (air transport)

Passenger-LQ: Y203

EQ : E0

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28, Entry 40, Entry 75

2004/42/EC (VOC):

100 % (925 g/l)

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

propan-2-ol; isopropyl alcohol; isopropanol

Safety Data Sheet

according to Regulation (EC) No 1907/2006

MET-L-CHEK Developer D70 Spray

Revision date: 05.06.2023

Page 10 of 11

SECTION 16: Other information**Changes**

section 1, 11, 12, 16

Abbreviations and acronyms

CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
IMDG: International Maritime Code for Dangerous Goods
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Key literature references and sources for data

General review and adaption to regulation (EC) 2020/878

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product

Safety Data Sheet

according to Regulation (EC) No 1907/2006

MET-L-CHEK Developer D70 Spray

Revision date: 05.06.2023

Page 11 of 11

named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)