

according to Regulation (EC) No 1907/2006

MET-L-CHEK Spezialreiniger NPU Spray

Revision date: 27.06.2023 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

MET-L-CHEK Spezialreiniger NPU Spray

Further trade names

Article no. (user): 121.100.101

UFI: 96K5-KXAV-DQ68-V1EN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Washing and cleaning products (including solvent based products)

1.3. Details of the supplier of the safety data sheet

Company name: Helling GmbH
Street: Spoekerdamm 2
Place: D-25436 Heidgraben

Telephone: +49-4122-922-0 Telefax: +49-4122-922-201

e-mail: info@helling.de Internet: www.helling.de

1.4. Emergency telephone Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Hazard categories: Aerosols: Aerosol 1

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes serious eye irritation.

May cause drowsiness or dizziness.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol

propane butane

Signal word: Danger

Pictograms:





Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.



according to Regulation (EC) No 1907/2006

MET-L-CHEK Spezialreiniger NPU Spray

Revision date: 27.06.2023 Page 2 of 11

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name					
	EC No	Index No	REACH No			
	Classification (Regulation (E0	C) No 1272/2008)	·			
67-63-0	propan-2-ol; isopropyl alcoho	l; isopropanol		70 - 80 %		
	200-661-7	603-117-00-0	01-2119457558-25			
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336					
106-97-8	butane		17 - 25 %			
	203-448-7	601-004-00-0	01-2119474691-32			
	Flam. Gas 1; H220					
74-98-6	propane			3 - 5 %		
	200-827-9	601-003-00-5	01-2119486944-21			
	Flam. Gas 1; H220					

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Cond	. Limits, M-factors and ATE	
67-63-0	200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	70 - 80 %
	inhalation: L	C50 = 30 mg/l (dusts or mists); dermal: LD50 = 13400 mg/kg; oral: LD50 = 4570 mg/kg	
106-97-8	203-448-7	butane	17 - 25 %
	inhalation: L	C50 = 658 mg/l (dusts or mists)	
74-98-6	200-827-9	propane	3 - 5 %
	inhalation: L	C50 = > 20 mg/l (vapours)	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.



Helling GmbH

according to Regulation (EC) No 1907/2006

MET-L-CHEK Spezialreiniger NPU Spray

Revision date: 27.06.2023 Page 3 of 11

After contact with skin

Wash with plenty of water. Change contaminated clothing.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Provide adequate ventilation. Wear a self-contained breathing apparatus and chemical protective clothing.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosive.

6.3. Methods and material for containment and cleaning up

Other information

Ventilate affected area.

Flammable liquids: Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling



according to Regulation (EC) No 1907/2006

MET-L-CHEK Spezialreiniger NPU Spray

Revision date: 27.06.2023 Page 4 of 11

Advice on safe handling

Do not breathe gas/fumes/vapour/spray.

When using do not eat, drink or smoke.

Use only in well-ventilated areas.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition - No smoking.

Hints on joint storage

Do not store together with: Oxidizing agents, strong.

7.3. Specific end use(s)

Please refer to our internet website for more information: www.helling.de

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day		
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day		
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day		
Consumer DNEL, long-term		inhalation	systemic	89 mg/m³		
Worker DNEL,	, long-term	inhalation	systemic	500 mg/m³		

Additional advice on limit values

none

8.2. Exposure controls







according to Regulation (EC) No 1907/2006

MET-L-CHEK Spezialreiniger NPU Spray

Revision date: 27.06.2023 Page 5 of 11

Appropriate engineering controls

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

refer to chapter 7. No further action is necessary.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Before starting work, apply solvent-resistant skincare preparations.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Skin protection

Body protection: not required.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Environmental exposure controls

No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: colourless
Odour: Alcohol

Test method

Melting point/freezing point:

Boiling point or initial boiling point and

not applicable
not applicable

boiling range: Flammability

Solid/liquid: not applicable
Gas: not applicable
Lower explosion limits: 1,4
Upper explosion limits: 10,8
Flash point: not applicable

Auto-ignition temperature: not determined ASTM D 1929

pH-Value: not applicable Viscosity / kinematic: not applicable Water solubility: partially soluble

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: 4000 hPa

(at 20 °C)

Density: 0,755 g/cm³

9.2. Other information

Explosive properties not explosive.

Other safety characteristics

Solvent separation test:

Solvent content:

70 - 80 %

Viscosity / dynamic:

not applicable

not applicable

Further Information



according to Regulation (EC) No 1907/2006

MET-L-CHEK Spezialreiniger NPU Spray

Revision date: 27.06.2023 Page 6 of 11

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No risks worthy of mention.

10.2. Chemical stability

No risks worthy of mention.

10.3. Possibility of hazardous reactions

Vapours may form explosive mixtures with air.

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

10.5. Incompatible materials

Oxidizing agents, strong.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
67-63-0	propan-2-ol; isopropyl a	lcohol; isop	ropanol					
	oral	LD50 mg/kg	4570	Rat				
	dermal	LD50 mg/kg	13400	Rabbit				
	inhalation (4 h) dust/mist	LC50	30 mg/l	Rat				
106-97-8	butane							
	inhalation (4 h) dust/mist	LC50	658 mg/l	Rat				
74-98-6	propane							
	inhalation (4 h) vapour	LC50	> 20 mg/l	Rat				

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

MET-L-CHEK Spezialreiniger NPU Spray

Revision date: 27.06.2023 Page 7 of 11

11.2. Information on other hazards

Endocrine disrupting properties

see section 12

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol							
	Acute fish toxicity	LC50 mg/l	8970		Leuciscus idus (golden orfe)			
	Acute algae toxicity	ErC50 mg/l	>1000		Scenedesmus subspicatus			
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h	Daphnia magna			
	Acute bacteria toxicity	(EC50 mg/l)	>100					
74-98-6	propane							
	Acute fish toxicity	LC50 mg/l	> 100	96 h				
	Acute algae toxicity	ErC50 mg/l	> 100					
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h				

12.2. Persistence and degradability

Easily biodegradable (concerning to the criteria of the OECD)

12.3. Bioaccumulative potential

Based on the n-octanol/water partition coefficient significant accumulation in organisms is not expected.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
74-98-6	propane	2,36

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not empty into drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific



according to Regulation (EC) No 1907/2006

MET-L-CHEK Spezialreiniger NPU Spray

Revision date: 27.06.2023 Page 8 of 11

to the industry and process.

List of Wastes Code - residues/unused products

WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE

CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal

packaging waste); metallic packaging

Contaminated packaging

Water (with cleaning agent). Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1950 **AEROSOLS** 14.2. UN proper shipping name:

14.3. Transport hazard class(es): 14.4. Packing group: Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L Excepted quantity: E0 Transport category: 2 Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950 14.2. UN proper shipping name: **AEROSOLS**

14.3. Transport hazard class(es): 2 14.4. Packing group: 2.1 Hazard label:



5F Classification code:

190 327 344 625 Special Provisions:

Limited quantity: 1 I Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950 14.2. UN proper shipping name: **AEROSOLS**

14.3. Transport hazard class(es): 14.4. Packing group: Hazard label: 2.1



2.1



according to Regulation (EC) No 1907/2006

MET-L-CHEK Spezialreiniger NPU Spray

Revision date: 27.06.2023 Page 9 of 11

Special Provisions: 63, 190, 277, 327, 344, 381, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G Passenger LQ: Y203 Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

none

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28, Entry 40, Entry 75

2004/42/EC (VOC): 100 % (755 g/l)

Additional information

aerosol directive (75/324/EEC).

Safety data sheet available for professional user on request.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out: propan-2-ol; isopropyl alcohol; isopropanol

SECTION 16: Other information



according to Regulation (EC) No 1907/2006

MET-L-CHEK Spezialreiniger NPU Spray

Revision date: 27.06.2023 Page 10 of 11

Changes

section 9

Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LC50: Lethal concentration, 50% LD50: Lethal dose, 50%

LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules MFAG: Medical First Aid Guide

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Key literature references and sources for data

General review and adaption to regulation (EC) 2020/878

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of





according to Regulation (EC) No 1907/2006

MET-L-CHEK Spezialreiniger NPU Spray

Revision date: 27.06.2023 Page 11 of 11

processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)